

Low Reflection View Perfection

Night Vision



Benefits

- Great heat rejection helps provide energy savings and improved comfort
- Enhanced views with low interior reflectivity, especially at night
- Helps reduce glare and eye discomfort
- Helps extend the life of furnishings by significantly reducing harmful UV rays, the largest cause of fading
- Excellent scratch resistant coating
- 3M nanotechnology enhances color stability
- Comprehensive warranty from 3M

Energy Savings	★★★★
Heat Rejection	★★★★
Glare Reduction	★★★★
Visible Reflection	★★★

In comparison to other 3M™ Sun Control Window Films

Best ★★★★★ Better ★★★ Good ★★ Fair ★

Valued Associations & Alliances



Night Vision Case Study

Embarcadero Center, San Francisco, California

Climate Zone 3

345,000 sq ft installation of Night Vision 25





Payback period — less than 1 year

Customer Issues:

- High energy costs and consumption
- Tenant comfort issues due to direct sun



Product Performance & Technical Data

Glass Type (All 1/4")	Film Type	Visible Light			Total Solar Energy Rejected	Solar Heat Gain Coefficient	U Value	Solar Heat Reduction	UV Light Rejected	Glare Reduction	Visible Light to Solar Heat Gain Ratio
		Reflected (Interior)	Reflected (Exterior)	Transmitted							
 Clear	Night Vision 15	11%	38%	15%	72%	0.28	0.98	66%	99%	83%	0.5
	Night Vision 25	7%	19%	24%	61%	0.39	1.00	52%	99%	73%	0.6
	Night Vision 35	7%	13%	36%	52%	0.48	1.03	41%	99%	59%	0.7
 Tinted	Night Vision 15	11%	16%	9%	70%	0.30	0.98	52%	99%	82%	0.3
	Night Vision 25	7%	10%	14%	64%	0.36	1.00	43%	99%	74%	0.4
	Night Vision 35	6%	8%	22%	58%	0.42	1.03	33%	99%	58%	0.5
 Double Clear	Night Vision 15	11%	39%	14%	60%	0.40	0.46	43%	99%	82%	0.4
	Night Vision 25	8%	24%	22%	51%	0.49	0.47	29%	99%	72%	0.4
	Night Vision 35	8%	19%	32%	45%	0.55	0.47	21%	99%	60%	0.6
 Double Tinted	Night Vision 15	11%	17%	8%	68%	0.32	0.46	37%	99%	83%	0.3
	Night Vision 25	8%	12%	13%	63%	0.37	0.47	27%	99%	73%	0.4
	Night Vision 35	7%	10%	19%	59%	0.41	0.47	19%	99%	60%	0.5

LEED Certification

Window films may be used towards the following LEED credits:

- SS-8
- EA-1
- MR 1.1-1.2
- MR 5.1-5.2
- EQ-7.1
- EQ-7.2
- EQ-8.1-8.2
- ID

Warranty, Limited Remedy and Disclaimer: 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. **3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES OR CONDITIONS, INCLUDING ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If the 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. **Limitation of Liability:** Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.



3M Renewable Energy Division Window Films

3M Center, Building 235-2S-27
St. Paul, MN 55144-1000
3M.com/windowfilm

3M and Night Vision are trademarks of 3M Company. Used under license in Canada.
Please recycle. Printed in U.S.A. © 3M 2014. All rights reserved. 98-0150-0314-2